

# CoolAssist

# Fan Assisted Floor Tiles

## Fan Specifications

<b>Wall ring:</b>	Die Cast Aluminum
<b>Blades:</b>	Sheet Steel, Coated in Black
<b>Number of Blades:</b>	7
<b>RPM:</b>	2550
<b>Rating:</b>	60,000 Hours @ 86° F
<b>Approvals:</b>	VDE, UL, CSA, CCC, GOST
<b>Type of protection:</b>	IP 44
<b>Insulation Class:</b>	B
<b>Bearings:</b>	Maintenance-Free Ball Bearings
<b>Motor Protection:</b>	TOP Wired Internally
<b>Product Class:</b>	I
<b>Product Conforming to Standards:</b>	EN 60335-1, CE



### AirFlow Evaluation #1

Under Floor Static Pressure  
.029" H<sup>2</sup>O

Air Flow with CoolAssist

<b>High:</b>	1696 CFM
<b>Medium:</b>	1410 CFM
<b>Low:</b>	960 CFM
<b>Off:</b>	539 CFM

### AirFlow Evaluation #2

Under Floor Static Pressure  
.013" H<sup>2</sup>O

Air Flow with CoolAssist

<b>High:</b>	1508 CFM
<b>Medium:</b>	1350 CFM
<b>Low:</b>	725 CFM
<b>Off:</b>	240 CFM

<b>Voltage:</b>	120V (220V also available)
<b>Current:</b>	Low Speed 0.86 Amps, High Speed 1.28 Amps Inrush 2.9 Amps to 2.3 Amps in 5 Seconds
<b>Dimensions:</b>	22.24" x 22.24" x 3.74"
<b>Weight:</b>	31.97lbs
<b>Warranty:</b>	1 year

Product designed, manufactured and assembled in an ISO9001 certified manufacturing environment.




(800) 328-2256

For more information, please visit [www.dataclean.com](http://www.dataclean.com)



- **A GREEN SOLUTION**
- **400% MORE AIRFLOW**
- **VARIABLE SPEED**
- **EFFICIENT**



# CoolAssist

## Give Your Equipment The *CoolAssist* It Needs!

*CoolAssist* can deliver up to four times the volume of cool conditioned air compared to standard perforated panels or even high-volume panels. *CoolAssist* provides extra cooling to those hard to cool areas where high-density servers have created hot spots. Additionally, *CoolAssist* will deliver the air all the way to the top of the rack. The adjustable speed control provides variable airflow to match the amount of cooling needed. Fan speed adjustment is made quick and easy from the top of the floor tile.

*CoolAssist* requires no down time or movement of racks for installation and one unit can provide cooling for two or three adjacent racks. Multiple units can be used at the same time if larger areas require additional cooling.

*CoolAssist* is a Green solution. Many data centers are kept cooler than necessary just to handle a few high-density areas. *CoolAssist* can manage those hot spots without requiring an over-cooled data center.

Let Data Clean provide your equipment a *CoolAssist*.

### CoolAssist Specifications

- Universally Adaptable to Most Floors
- 400% More Airflow
- Easy Airflow Adjustment from the Top of the Tile
- 120v
- 1 Year Warranty

### Options:

- Data Clean Infinity Air Grate – High-Volume Perforated Panel
- 220v Version
- 2 Fan Version

For Detailed Mechanical Specifications Please Visit [www.dataclean.com/coolassist.htm](http://www.dataclean.com/coolassist.htm)

**For Sales and Installation, contact:**



(800) 328-2256 • [www.dataclean.com](http://www.dataclean.com)